

US 2 Trestle Capacity Improvements & Westbound Trestle Replacement PEL Study

TECHNICAL WORKING GROUP (TWG) MEETING #3

January 27, 2025

Safety Moment



SAFETY

TAKE 2 TO THINK IT THROUGH

wsdot.wa.gov/safety




Introductions

Please introduce yourself in the chat: Name, Organization, Role


Organizations invited today:

- Boeing
- City of Everett
- City of Lake Stevens
- City of Marysville
- City of Snohomish
- Community Transit
- Economic Alliance of Snohomish County
- Everett Transit
- FHWA
- Muckleshoot Tribe
- Port of Everett
- PSRC
- Sauk-Suiattle Tribe
- Snohomish County
- Snoqualmie Indian Tribe
- Stillaguamish Tribe
- Suquamish Tribe
- Swinomish Tribe
- Tulalip Tribes
- Washington State Department of Health
- Washington State Patrol
- Washington State Transportation Commission
- WSDOT
- Washington Trucking Association
- Yakama Tribe

US 2 Trestle PEL Study Status



Summary Milestone Schedule



*Meeting Series 2 and 4 will only be TWG meetings - No RAC or EAG meetings at these times

TWG Meeting Progression

We are here

TWG/EAG/ RAC #1

- Purpose and Need statement
- Existing and future No Build transportation conditions

TWG #2

- Analysis framework and screening criteria
- Review options for Pre-screening & Level 1 screening

TWG #3 EAG/RAC #2

- Environmental existing conditions
- Pre-screening & Level 1 screening results
- Discuss packaging concepts into Level 2 system alternatives

TWG #4

- Level 2 screening analysis update

TWG #5 EAG/RAC #3

- Level 2 evaluation results and potential effects and benefits

TWG #6 EAG/RAC #4

- PEL Study findings, alternatives to take into NEPA, next steps

TWG = Technical Working Group
EAG = Executive Advisory Group
RAC = Resource Agency Committee

TWG Meeting #3 Purpose

Seek input on:

- Active transportation concepts and integration
- Pre-screening and Level 1 screening results
- Process to develop preliminary system-level alternatives

Agenda

- Study progress
- Review results of Pre-screening and Level 1 screening of concepts
- Discuss Level 2 screening and forming system alternatives
- Environmental existing conditions
- Next steps and adjourn


Study Progress: Prescreening and Level 1 results

TWG Meeting #2 Recap

- Reviewed final Purpose & Need statements
- Introduced analysis framework and screening criteria
- Introduced existing and future No Build conditions
- Previewed concepts and took suggestions for edits

Concept Evaluation Update

Process to develop a reasonable range of alternatives that meet the Purpose and Need



Prescreening Results

Study concepts eliminated through prescreening:

- **TW1:** *Retrofit existing structure*
Two 11' GP lanes with 2' inside shoulder and 8.25' outside shoulder.
 - Fails multiple mobility and resiliency criteria
- **TW8:** *SR 526 Extension*
New east-west corridor extending SR 526 from I-5 to SR 9 south of the US 2 trestle.
 - Fails multiple resiliency criteria in the US 2 corridor

Qualitative Level 1 Criteria: Vehicular

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Vehicle delay	H: Substantial improvement compared to No Build M: Somewhat lower delay as No Build L: Similar or Worse delay than No Build
Travel time reliability	H: Substantial improvement compared to No Build M: Somewhat better reliability compared to No Build L: Similar or Worse reliability compared to No Build
Effect on vulnerable populations and overburdened communities (VPOC)	H: Improves transportation access for VPOCs M: Similar transportation access for VPOCs L: Worsens transportation access for VPOCs

Qualitative Level 1 Criteria: Freight

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Delay for freight vehicles	H: Substantial improvement compared to No Build M: Somewhat lower delay as No Build L: Similar or worse delay than No Build
Freight travel time reliability	H: Substantial improvement compared to No Build M: Somewhat better reliability compared to No Build L: Similar or Worse reliability compared to No Build

Qualitative Level 1 Criteria: HOV and Transit

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Transit/HOV delay	H: Substantial improvement compared to No Build M: Somewhat lower delay as No Build L - Similar or worse delay than No Build
Transit system accessibility and connectivity	H: Substantial improvement compared to No Build M: Somewhat better compared to No Build L: Similar or worse than No Build
Transit travel time reliability	H: Substantial improvement compared to No Build M: Somewhat better reliability compared to No Build L: Similar or worse reliability compared to No Build
Corridor person throughput	H: Substantial improvement compared to No Build M: Somewhat better compared to No Build L: Similar or worse person throughput compared to No Build

Qualitative Level 1 Criteria: Active Transportation

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Direct route to key destinations	<p>H: Most direct route, little to no out of direction travel to destination(s) M: Average of about 20% of route is out of direction travel to destination(s) L: Average of more than 50% of route is out of direction travel to destination(s)</p>
Elevation changes	<p>H: Minimal change in elevation M: Some change in elevation at a low grade L: Alignment has a significant change in elevation (multiple overpasses, hills)</p>
Connections to existing or planned AT facilities	<p>H: Multiple connections to planned or existing AT facilities without new on-street connections M: One connection to planned or existing AT facilities without new on-street connections L: Connects to planned or existing AT facilities with new on-street connections</p>

Multimodal Mobility

Qualitative Level 1 Criteria: Safety

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Motorized vehicle safety	H: Substantial improvement compared to No Build M: Moderate improvement to motorized vehicle safety L: No improvement in motorized vehicle safety
AT conflicts with motorized vehicles at intersections	H: No conflict points with motor vehicles M: Alignment passes through intersections, but no ramp terminals L: Alignment passes through multiple intersections including ramp terminals
Visibility for AT modes (CPTED)	H: Substantial improvement in visibility for AT compared to No Build M: Moderate improvement in visibility for active transportation modes L: Similar or worse visibility for active transportation modes
Safety of access to transit facilities	H: Substantial improvement compared to No Build M: Moderate improvement in safety of access to transit facilities L: No improvement in safety of access to transit facilities

Notes: CPTED = Crime Prevention through Environmental Design

Safety

Qualitative Level 1 Criteria: Seismic Resilience

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Seismic resiliency	H: Substantial improvement in seismic resiliency compared to No Build M: Moderate improvement in seismic resiliency compared to No Build L: No improvement in in seismic resiliency compared to No Build

Resilience

Qualitative Level 1 Criteria: Asset Management

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Asset management	<p>H: Improves 2 or more of the focus infrastructure areas (roadway, stormwater, structural) compared to No Build and reduces logjam occurrences under bridge(s) across Ebey Slough (east end concepts only)</p> <p>M: Improves at least one of the 3 infrastructure focus areas or reduces logjam occurrences under bridge(s) across Ebey Slough (east end concepts only)</p> <p>L: Similar or Worse than No Build in terms of corridor infrastructure state of repair and frequency of logjam occurrences under bridge(s) across Ebey Slough (east end concepts only)</p>

Qualitative Level 1 Criteria: Climate and Natural Hazard Resilience

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Climate/ natural hazard resilience	H: Substantially improves drainage design to prevent standing water compared to No Build M: Moderately improves drainage design to prevent standing water L: Similar or worse than No Build in terms of drainage design and preventing standing water


Resilience

Qualitative Level 1 Criteria: Operational Resilience

<i>Level 1 Criteria</i>	<i>Level 1 Scoring</i>
Operational resilience	<p>H: Substantial amount of shoulder provided compared to No Build and additional ramp connections to downtown Everett for west end concepts</p> <p>M: Some additional shoulder space provided compared to No Build or additional ramp connections to downtown Everett (for west end concepts)</p> <p>L: Similar or less shoulder space compared to No Build and no additional ramp connections to downtown Everett (for west end concepts)</p>

Resilience

Multimodal Concepts Screened in Level 1




What's changed?

Modifications since we last met:

- Westbound ramps to California open in all concepts
- Ramp meters included on ramps to I-5
- No HOV ramp meter bypasses except transit routes
- Additional Active Transportation concepts

Active Transportation Integration



Level 1 Screening: Rating Process

Multimodal criteria derived from purpose and need statement


Multimodal concepts are rated as High (H), Medium (M) or Low (L) across all

Highest rated multimodal concepts are those that score higher than the average score


		Multimodal Concepts					
Purpose & Need	Roadway Concept	A	B	C	D	E	F
	AT Concept Pairing	1	2	3	2	5	4
	Criteria 1	M	M	H	H	M	L
	Criteria 2	H	M	H	L	L	M
	Criteria 3	L	H	H	M	L	M
	Criteria 4	H	L	M	H	M	L
	↓	↓	↓	↓	↓	↓	↓
	Criteria 19	L	M	L	M	H	H
	Total Score (H=3, M=2, L=1)	scoreA	scoreB	scoreC	scoreD	scoreE	scoreF
	Above Avg Score?	Yes	No	Yes	Yes	No	No

Highest rated concepts are A, C and D


Level 1 Screening: Summary of Preliminary Screening Results




Level 1 Screening: Summary Results for West Interchange




Level 1 Draft Screening Results: West Interchange - WB




Level 1 Draft Screening Results: West Interchange - WB



Level 1 Draft Screening Results: West Interchange - WB




Level 1 Draft Screening Results: West Interchange - WB




Level 1 Draft Screening Results:

West Interchange - EB




Level 1 Screening: Summary Results for the Trestle



Level 1 Screening Preliminary Results: Westbound Trestle Highest Rated Roadway Concepts (4)


TW3 – New structure

3 GP lanes, full shoulders




TW4 – New structure

2 GP lanes, 1 HOV lane, full shoulders




TW5 – New structure

3 GP lanes, 1 Peak Use HOV/transit shoulder, full shoulders on both sides during off-peak



TW6 – New structure

2 GP lanes, 1 reversible HOV/transit lane, design-standard shoulders




All concepts would be paired with TR-AT-04 for active transportation

Draft

Level 1 Screening Preliminary Results: Eastbound Trestle Highest Rated Roadway Concepts (4)


TE4 – New structure

2 GP lanes, Peak Use transit shoulder




TE5 – New structure

3 GP lanes, full shoulders




TE6 – New structure

2 GP lanes, 1 HOV lane, full shoulders



TE7 – New structure


3 GP lanes, Peak use HOV/transit shoulder




All concepts would be paired with TR-AT-06 for active transportation

Draft

Level 1 Screening: Summary Results for East Interchange




Level 1 Draft Screening Results: East Interchange - WB




Level 1 Draft Screening Results: East Interchange - WB

EW4 & EE-AT-05

-  Roadway Concept
-  Active Transportation **Draft**
-  Local Street
-  Roadway Under Existing Bridge



Level 1 Draft Screening Results: East Interchange - WB




Level 1 Draft Screening Results:

East Interchange - EB




Level 1 Draft Screening Results:

East Interchange - EB



System-level Alternatives Development

Developing Level 2 System Alternatives






Traffic Sensitivity Testing

1. Identify interchange concepts that provide similar "benefit" and could be compared with simple traffic operations analysis
2. Outline single hour to evaluate the concepts
3. Cut VISSIM model to focus on specific area (save time running models)
4. Compare output for travel time and delay
5. Rank concepts by performance

Example: *Compare two concepts that show two different access points to City of Everett. How well do they perform during morning peak hour? Could also compare with a single access point to the City.*

Example System Alternative



- Roadway Concept
- HOV Lane
- Active Transportation
- Local Street
- ⋯ Roadway Under Existing Bridge

Draft



Draft Level 2 Evaluation Criteria: Vehicular

Level 2 Draft Evaluation Criteria	General Methodology
Travel Times	<ul style="list-style-type: none"> • Peak hour travel times between set origin-destination (OD) pairs using output from VISSIM or DTA model
Person Hours of Delay	<ul style="list-style-type: none"> • Peak hour person hours of delay within the study model analysis area as produced by the DTA model or VISSIM model
Hours of Congestion	<ul style="list-style-type: none"> • Assess how many hours out of a typical weekday that the US 2 trestle and its connecting interchanges are congested. Use SoundCast model hourly volumes and v/c ratios as measures. v/c
Travel time reliability	<ul style="list-style-type: none"> > 0.9 = congested hour
Travel times between VPOCs and essential services*	<ul style="list-style-type: none"> • General purpose reliability qualitatively based on changes in congestion levels and improved ability to clear disabled vehicles (e.g., wide enough shoulders), and reduced potential of crashes and logjam clearing impacts • Travel time related to VPOCs based on SoundCast model (SoundCast model used to provide flexibility in OD zone locations and differing times of day travel may be made)

**Note: VPOC zones and associated OD pairs to be analyzed, including locations of essential services, in the criteria below will be informed by data compiled in the Environmental Existing Conditions and Environmental Effects and Benefits Reports and developed with input from project stakeholders, including community-based organizations (CBOs.)*

Draft Level 2 Evaluation Criteria: Freight

<i>Level 2 Draft Evaluation Criteria</i>	<i>General Methodology</i>
Freight peak period delay	<ul style="list-style-type: none">• Freight travel times based on VISSIM or DTA model results• Freight travel reliability qualitatively based on changes in congestion levels and improved ability to clear disabled vehicles (e.g., wide enough shoulders)
Freight travel time reliability	

Draft Level 2 Evaluation Criteria: HOV and Transit

<i>Level 2 Draft Evaluation Criteria</i>	<i>General Methodology</i>
Transit travel time	<ul style="list-style-type: none"> • Peak hour travel times for transit routes using the US 2 trestle based on output from VISSIM or DTA model • Person throughput based on transit and HOV modes of travel from the SoundCast model and assumed vehicle occupancy for each mode • Transit/HOV reliability based on degree of transit/HOV lanes/priority strategies provided or if in mixed traffic changes in congestion levels, improved ability to clear disabled vehicles (e.g., wide enough shoulders) • Transit system accessibility and connectivity measured by number of new or improved transit access facilities, new or improved transit connections provided, including new park-and-ride lot capacity
Person throughput (persons/hour)	
Transit travel time reliability	
Improved accessibility and connectivity	

Draft Level 2 Evaluation Criteria: Active Transportation

Level 2 Draft Evaluation Criteria	General Methodology
Level of traffic stress (LTS) for bicycles and pedestrians	<ul style="list-style-type: none"> • Bicycle & Pedestrian Level of traffic stress (LTS) for routes accessing the trestle corridor and on the trestle corridor • Directness of route measured by how much out of direction travel is required • Elevation changes qualitatively assessed based on number of hills encountered and steepness of grade • Active transportation connections based on degree of connection to local active transportation networks and the trestle, and along the US 2 trestle corridor
Directness of route to key destinations	
Elevation changes	
Active transportation connections	

Draft Level 2 Evaluation Criteria: Safety Need

<p><i>Level 2 Draft Evaluation Criteria</i></p>	<p><i>General Methodology</i></p>
<p>Motorized Vehicle Safety:</p> <ul style="list-style-type: none"> • Predicted Crash Analysis • Transit /HOV safety 	<ul style="list-style-type: none"> • Daily traffic volumes will be based on output from the SoundCast model. Daily volumes and geometric cross-sections will be included in the ISATe analysis. • Will not assess safety for HOV facilities quantitatively (unable to); will instead assess qualitatively via speed differential considerations, conflict points, and lane changes.
<p>Active Transportation Safety:</p> <ul style="list-style-type: none"> • Bicycle Safety • Pedestrian Safety 	<ul style="list-style-type: none"> • Qualitative assessment of effects of changes for pedestrian and bicycle safety using a comparison of traffic volumes, conflict points, and applicable crash modification factors (CMFs) associated with design.

Safety

Draft Level 2 Evaluation Criteria: Seismic Resilience

<i>Level 2 Draft Evaluation Criteria</i>	<i>General Methodology</i>
Seismic resilience	<ul style="list-style-type: none">• Percentage of corridor that meets current seismic design criteria

Resilience

Draft Level 2 Evaluation Criteria: Asset Management

<i>Level 2 Draft Evaluation Criteria</i>	<i>General Methodology</i>
Asset Management	<ul style="list-style-type: none">• Percentage of the corridor that meets current roadway design standards & structural standards• Ability of alternative to affect the reduction of logjam occurrences under the bridge(s) across Ebey Slough

Resilience

Draft Level 2 Evaluation Criteria: Climate and Natural Hazard Resilience

<i>Level 2 Draft Evaluation Criteria</i>	<i>General Methodology</i>
Climate and natural hazard resilience	<ul style="list-style-type: none">• Percentage of the corridor that meets current drainage design standards

Resilience

Draft Level 2 Evaluation Criteria: Operational Resilience

<i>Level 2 Draft Evaluation Criteria</i>	<i>General Methodology</i>
Operational resilience	<ul style="list-style-type: none">• Percentage of corridor roadway that has design standard shoulder widths and pull-outs provided• Provision of redundancy in connections into downtown Everett


Resilience

Environmental Existing Conditions


Environmental Existing Conditions Report Topics

1. Earth (geology and soils)
2. Air quality
3. Greenhouse gas emissions
4. Stormwater best management practice sites and retrofit priorities
5. Wetlands and other waters (including mitigation sites and navigable waters)
6. Chronic environmental deficiencies
7. Climate vulnerability
8. Special flood hazard areas
9. Habitat connectivity
10. Fish passage barriers
11. Threatened and endangered species (plants and wildlife)
12. Noise walls
13. Hazardous materials contamination sites
14. Publicly owned parks, recreational areas, and refuges
15. Cultural resources
16. Environmental Justice/HEAL Act (community profile)

Environmental Existing Conditions Earth (Geology and Soils)



Environmental Existing Conditions Wetlands and WSDOT Environmental Mitigation Sites




LEGEND

- Preliminary Study Area
- City of Everett Wetland
- Snohomish County Wetland
- City of Lake Stevens Wetland

NWI Wetland Type



- Estuarine and Marine Deepwater
- Estuarine and Marine Wetland
- Freshwater Emergent Wetland

- Freshwater Forested/ Shrub Wetland
- Freshwater Pond
- Lake
- Riverine




LEGEND

- Preliminary Study Area
- Environmental Mitigation Site





Environmental Existing Conditions

Navigable Waterways and Flood Zones




Environmental Existing Conditions

Essential Fish Habitat and Fish Passage Barriers



Environmental Existing Conditions Report


Hazardous Material Sites and Parks and Recreation Areas



Environmental Existing Conditions Report



Environmental Justice/HEAL Act

- Community profile of larger demographic study area, consistent with community engagement area
- Community resources identified within Preliminary Study Area



Environmental Existing Conditions Report

Environmental Justice/HEAL Act



Next Steps

Community Engagement Milestones

Timeline	Outreach Milestones
Winter 2024	<ul style="list-style-type: none">✓ Publish website✓ Finalize communications plan✓ Conduct listening sessions
Spring 2024	<ul style="list-style-type: none">✓ Establish and facilitate first PEL committee meetings✓ Purpose and Need online open house
Summer/Fall 2024	<ul style="list-style-type: none">✓ TWG Meeting 2✓ Online open house follow-up
Winter 2025	<ul style="list-style-type: none">❑ TWG Meeting 3 and EAG/RAC Meeting 2
Spring/Summer 2025	<ul style="list-style-type: none">❑ Public review of draft alternatives
Winter 2026	<ul style="list-style-type: none">❑ Public review of the draft PEL report

PEL Committee Meeting Schedule

TWG/EAG/RAC #1

- Purpose and Need statement
- Existing and future No Build transportation conditions

TWG #2

- Analysis framework and screening criteria
- Review options for pre-screening & Level 1 screening

TWG #3 EAG/RAC #2

- Environmental existing conditions
- Pre-screening & Level 1 screening results
- Discuss packaging concepts into Level 2 system alternatives

TWG #4

- Level 2 analysis update



Next Meeting

TWG #5 EAG/RAC #3

- Level 2 evaluation results and potential effects and benefits

TWG #6 EAG/RAC #4

- PEL Study findings, alternatives to take into NEPA, next steps

TWG = Technical Working Group
EAG = Executive Advisory Group
RAC = Resource Agency Committee

Thank you!

Send comments/questions to:

Jennifer Rash

Study Engagement

rashjen@consultant.wsdot.wa.gov

Oteberry Kedelty

WSDOT Project Manager

KedeltO@wsdot.wa.gov

Meeting materials posted on the study website:

https://wsdot.wa.gov/construction-planning/search_projects/us-2-trestle-capacity-improvements-westbound-trestle-replacement